



ILLI (LX-IL)

TYPE: LX-IL-

KEY FEATURES


- High-performance lumen output
- UGR<19
- Highly effective noise absorption
- 2 sizes and a wide range of colors
- 9' / 2740mm length of black woven power cable per fixture
- IES photometric files available
- Some assembly required

OPTIONAL EXTRAS


- Additional options available upon request:
- E26/E27
 - White canopy and power cord

SIZE, OUTPUT AND WEIGHT


LANDSCAPE (L)



PORTRAIT (P)



LUMINOUS INTENSITY DISTRIBUTION



LANDSCAPE AND PORTRAIT	
Delivered Lumen Output	2267 lm
Wattage	25.9 W
Efficacy	87.5 lm/W
CRI	90+
UGR	<19
Beam Angle	45°
CCT	3000/3500/4000 K
Weight	11lbs / 5Kg

ORDER CODE

EXAMPLE: LX - IL - L - FG - 40 - UNV - RD


(Luxxbox illi, Landscape (26" x 15" / 665mm x 380mm), Forest Green, 4000K, Universal 110-277V / 0-10V 1% dimming (North America only), Remote Driver

LX - IL	SIZE		SHADE COLOR	COLOR TEMP		REGION / DIMMING		DRIVER TYPE	
IL	L	LANDSCAPE (26" x 15" / 665mm x 380mm)	Use color codes as shown	30	3000K	UNV	Universal 110 - 277V / 0-10V 1% Dimming (North America only)	CD	Canopy concealed driver (UNV/North America only)
	P	PORTRAIT (19" x 23" / 488mm x 578mm)		35	3500K				
				40	4000K	G	Global 220-240V 1% DSI/DALI dimming	RD	Remote driver (UNV or G)

AVAILABLE COLORS

Colors are subject to lead times and variations across batches

CORE



DESIGNER



Luxxbox reserves the right to change the specification, material and colors at any time without notice. Standard warranty terms and conditions apply. All rights reserved © All dimensions and values on specification sheet are nominal. November 2024. LX-IL-Spec-Sheet v4.3



LUXXBOX USA INC × (P)+1 (415) 871 0448 × USA@LUXXBOX.COM
 LUXXBOX PTY LTD × (P)+61 7 3257 2822 × INFO@LUXXBOX.COM
 WWW.LUXXBOX.COM





ILLI (LX-IL)


TYPE: LX-IL-

PHOTOMETRICS

LIGHT SOURCE SPECIFICATIONS

	LANDSCAPE AND PORTRAIT
Delivered Lumen Output	2267 lm
Wattage	25.9 W
Efficacy	87.5 lm/W
CRI	90+
UGR	<19
Beam Angle	45°
CCT	3000/3500/4000 K

LUMINOUS INTENSITY DISTRIBUTION PORTRAIT / LANDSCAPE






DRIVER INFORMATION

REGION/DIMMING	SIZE	WATTAGE (W)	MAX VOLTAGE (V)	COMPLIANCE
UNIVERSAL (UNV) 0-10V - 10% dimming 110 - 277VAC <i>(North America only)</i>	PORTRAIT	28.5 W	28-42VDC	
	LANDSCAPE			
GLOBAL (G) 0-10V - 1% dimming 220 - 240VAC DSI DALI	PORTRAIT	28.5 W	28-42VDC	
	LANDSCAPE			

CANOPY INFORMATION

Please note power cord and canopy will always be supplied in black unless specified otherwise.

	UNV (North America)		G
SIZE	CD	RD	RD
PORTRAIT / LANDSCAPE	CD6	SA4	SB4



Luxxbox reserves the right to change the specification, material and colors at any time without notice. Standard warranty terms and conditions apply. All rights reserved © All dimensions and values on specification sheet are nominal. November 2024. LX-IL-Spec-Sheet v4.3



ILLI (LX-IL)

TYPE: LX-IL-

MATERIAL SPECIFICATIONS

COLOR FASTNESS TO LIGHT:	ISO 105-B02-1994 Rating: 6-7
FIRE TEST:	AS 1530.3 / ISO 9705: Group 1 / GB8624 B1 / ASTM E-84-14 (Class A, FSI:20 - SDI:450) / BS EN13501-1:2007+A1:2009 (B-s1, d0)
ENVIRONMENTAL:	PET achieves GreenTag Certification / GreenRate: Level A
THERMAL TRANSITION:	ASTM C518-2010. R- Value = 0.30 m ² K/W
SOUND ABSORPTION:	AS ISO 354 – 2006 / Noise reduction coefficient (NRC) = 0.85
VOC EMISSIONS:	ASTM D5116 Rate: < 0.01 mg/m ² /hr (7 days)

Please note some of these certificates will apply to specific colors.


PRODUCT ACOUSTIC PROPERTIES

Testing and post analysis procedures were carried out in accordance with the references detailed below:

AS ISO 354-2006 (R2016)	Acoustics—Measurement of sound absorption in a reverberation room
AS ISO 11654—2002	Rating of sound absorption—Materials and systems
ASTM C423-17	Standard Test Method for Sound Absorption and Sound Absorption Coefficients by the Reverberation Room Method
ASTM E795-16	Standard Practices for Mounting Test Specimens During Sound Absorption Tests
ISO 20189	Screens, furniture and single objects intended for interior use – Rating of sound absorption and sound reduction of elements based on laboratory measurements.


IMPERIAL SABINS

Frequency (Hz)	Sound Absorption Coefficient	PORTRAIT (P)	LANDSCAPE (L)
125	0.69	26.62	28.39
250	0.92	35.49	37.85
500	0.96	37.03	39.49
1000	0.76	29.32	31.27
2000	0.79	30.48	32.50
4000	0.74	28.55	30.44



METRIC SABINS

Frequency (Hz)	Sound Absorption Coefficient	PORTRAIT (P)	LANDSCAPE (L)
125	0.69	2.47	2.64
250	0.92	3.30	3.52
500	0.96	3.44	3.67
1000	0.76	2.72	2.90
2000	0.79	2.83	3.02
4000	0.74	2.65	2.83



The Sabin data shown above is in accordance with the latest International Standards for the rating of sound absorption and reduction. This is different from the classic methodology, which includes the calculation of the Noise Reduction Coefficient (NRC), the Sound Absorption Average (SAA), the Weighted Sound Absorption Coefficient (**aw**) and the Sound Absorption Class (SAC). However, to make it easier to compare against other products, we are including that information on the table on the right, which was calculated using the Horizontal Floor Area method. Fully detailed test reports are available upon request.

NRC	0.90
SAA	0.90
aw	0.8

Luxxbox reserves the right to change the specification, material and colors at any time without notice. Standard warranty terms and conditions apply. All rights reserved © All dimensions and values on specification sheet are nominal. November 2024. LX-IL-Spec-Sheet v4.3



LUXXBOX USA INC × (P)+1 (415) 871 0448 × USA@LUXXBOX.COM
 LUXXBOX PTY LTD × (P)+61 7 3257 2822 × INFO@LUXXBOX.COM
 WWW.LUXXBOX.COM





ILLI (LX-IL)

TYPE: LX-IL-



PRODUCT DIMENSIONS

Please note the dimensions shown below refer to the assembled product. This pendant will be shipped flat pack and requires assembly. For more information, download the Assembly and Installation Instructions document from the product's page at www.luxxbox.com


LANDSCAPE (L)

PORTRAIT(P)


BOTTOM



FRONT




15" / 380mm




23" / 578mm

TOP



Suspension (centered with pendant and canopy)



Ø26" / Ø665mm

Ø19" / Ø488mm

Luxxbox reserves the right to change the specification, material and colors at any time without notice. Standard warranty terms and conditions apply. All rights reserved © All dimensions and values on specification sheet are nominal. November 2024. LX-IL-Spec-Sheet v4.3



LUXXBOX USA INC × (P)+1 (415) 871 0448 × USA@LUXXBOX.COM
LUXXBOX PTY LTD × (P)+61 7 3257 2822 × INFO@LUXXBOX.COM
WWW.LUXXBOX.COM

